

**CLAIMS**

What is claimed is:

5           1.    A method for routing information over an optical  
network supporting multiple optical service models, the  
method comprising:

receiving a link state advertisement at a switch;  
checking flooding domain information to decide whether  
10 to broadcast or block propagation of the link state  
advertisement, wherein checking the flooding domain  
information comprises checking an optical UNI interface  
type, an optical interface descriptor, and available  
bandwidth; and  
15           accepting or rejecting the request based on the  
flooding domain information.

2.    The method of claim 1, wherein the optical  
interface descriptor includes a user termination point, a  
20 user contract identifier, a user group identifier, and a  
user service mode identifier.

3. The method of claim 2, wherein the link state advertisement includes the optical interface descriptor.

4. A method for routing information over an optical network supporting multiple optical service models, the method comprising:

receiving a link state advertisement including an incoming optical interface descriptor at an optical switch;  
checking outgoing link information;

10 flooding the link state advertisement over the outgoing link if the outgoing link information includes a first pre-defined value,

blocking the link state advertisement if the outgoing link information includes a second pre-defined value; and

15 comparing the incoming optical interface descriptor and the outgoing link information if the outgoing link information includes neither the first pre-defined value nor the second predefined value and flooding the link state advertisement only if the incoming optical interface  
20 descriptor includes a value matching the outgoing link information.

5. The method of claim 4, further comprising checking a user status identifier prior to transmitting a link state advertisement and determining from the status identifier whether the user is out of service, busy, testing, or idle.

5

6. The method of claim 5, further comprising blocking transmission of the link state advertisement if the user is out of service, busy, or testing, and completing transmission of the link state advertisement if the user is  
10 idle.

7. The method of claim 4, wherein the multiple optical service models comprise an overlay model, a peer-to-peer model, and an augmented model.

15

8. The method of claim 7, wherein the link state advertisement is an optical link state advertisement.

9. The method of claim 8, further comprising flooding  
20 the optical link state advertisement if the service mode of the outgoing link is the overlay mode or the peer-to-peer mode and blocking the link state advertisement if the

service mode of the outgoing link is the overlay mode.

10. The method of claim 7, wherein the link state advertisement is a service link state advertisement.

5

11. The method of claim 10, further comprising flooding the service link state advertisement in all service modes.

10

12. The method of claim 7, wherein the link state advertisement is neither a service link state advertisement or an optical link state advertisement.

15

13. The method of claim 12, further comprising blocking the optical link state advertisement if the service mode is overlay mode or augmented mode and flooding the link state advertisement if the service mode is the peer-to-peer mode.

20

14. The method of claim 4, wherein the incoming optical interface descriptor comprises a user termination point, a user group ID, a user contract identifier, and a

user network identifier.

15. The method of claim 14, wherein the outgoing link  
information includes a value selected from a first value for  
5 broadcasting, a second value for blocking, and a third  
value.

16. A system for routing information over an optical  
network having multiple optical service models, the system  
10 comprising:  
wavelength routing protocol means for flooding an  
optical link state advertisement to an optical switch;  
means for checking an optical interface descriptor and  
an administrative domain to determine whether to broadcast  
15 or block propagation of the link state advertisement; and  
wavelength distribution protocol means for issuing a  
connection request upon receiving a broadcast determination.

17. The system claim 16, further comprising OBCP means  
20 for flooding a service LSA.

18. The system of claim 16, wherein the wavelength

5           19. The system of claim 18, wherein the wavelength  
routing protocol comprises OSPF means for determining an  
optimal path.

20. A processor readable medium for providing

10 instructions to at least one processor for delivery the at least one processor to:

- receive a link state advertisement including an optical interface descriptor at a switch;
- check outgoing link information;
- 15 flood the link state advertisement if the outgoing link information includes a first pre-defined value;
- block the link state advertisement if the outgoing link information includes a second predefined value; and
- compare the incoming interface descriptor to the
- 20 outgoing link information if the outgoing link information includes neither the first pre-defined value nor the second pre-defined and flooding the link state advertisement only

Overall		Age		Sex		Education		Occupation		Income		Health		Lifestyle		Environment		Genetics	
Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD	Mean	SD
1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3	1.2	0.3
1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4	1.5	0.4
1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5	1.8	0.5
2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6	2.1	0.6
2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7	2.4	0.7
2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8	2.7	0.8
3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9	3.0	0.9
3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0	3.3	1.0
3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1	3.6	1.1
3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2	3.9	1.2
4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3	4.2	1.3
4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4	4.5	1.4
4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5	4.8	1.5
5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6	5.1	1.6
5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7	5.4	1.7
5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8	5.7	1.8
6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9	6.0	1.9
6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0	6.3	2.0
6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1	6.6	2.1
6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2	6.9	2.2
7.2	2.3	7.2	2.3	7.2	2.3	7.2	2.3	7.2											

Doc #: 211866; V. 0